





- NOTES:
- 1) MATERIAL: SEE TABLE B
 - 2) FINISH: NONE
 - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
 - 6) IDENTIFICATION: IDENTIFY WITH DART P/N "D3874-1" USING VIBRATING STYLUS
 - 7) WEIGHT: 1.5 lbs
 - 8) TOOLING: THERMOFORM PER MOLD DT9474 PER DART QSI 022. TRIM PER MOLD
 - 9) MINIMUM THICKNESS: 0.050" ON FLANGES AND 0.065" ELSEWHERE EXCEPT AS SHOWN

B

PART NUMBER	DESCRIPTION
D3874-1L02	F6006 SUEDE/POLISHED 701 BLACK LEXAN SHEET 0.125 THICK (REF DART SPEC MLEX.125-F6006-02)
D3874-1L08	90318 PROTECT-A-GLAZE 112 CLEAR LEXAN SHEET 0.118 THICK (REF DART SPEC MLEX.118-90318-08)

PRELIMINARY ISSUE

DESIGN	AK	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	AK		
CHECKED	VS	DRAWING NO.	REV. B3
MFG. APPR.	DL	D3874	SHEET 2 OF 3
APPROVED		TITLE	SCALE
DE APPR.		FLOOR PROTECTOR	NTS
DATE	14.04.10	COPYRIGHT © 2009 BY DART AEROSPACE LTD <small>THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	

